Approved For Release 2002/07/22: CIA-RDP80-00810A002300740009-6 CLASSIFICATION SECRET/GONTROL - U. S. OFFICIALS ONLY

STELLOFAX 35

SECURITY DEFORMATION CENTRAL INTELLIGENCE AGENCY

REPORT N

INFORMATION REPORT

CD NO.

25X1A

COUNTRY

East Germany

DATE DISTR.

SUBJECT

German Industrial Standards (DIN - Norman) NO. OF PAGES

30 October 1953

for Yuels

PLACE ACQUIRED

DATE OF

INFO.

25X1A

NO. OF ENCLS.

SUPPLEMENT TO REPORT NO

| T. | | 2 | 123 | 2 | | N I | | 111 | | | | 张 | 2 |
|---------|-------------|------------|--------|--------------------|---------|---------|--------|-------|---------------|---------|----------------|----------|------|
| | 885 DO | CHEE | TONT | King in S. With | PORN! | erion i | affec | nns | THE NA | TOWA | Logi | ENSE | á |
| 1.0 | 64 X) (1941 | A OF | THE C. | S. CODE | i. AS 8 | FERMOR | 20. 1 | TR VD | 电湿电散 [| REIGHT | AP 8 | Maria . | 377 |
| 10.2 | 1,434, 4 | 7F 175 | COALLE | STE TO | CRR | RCPIPT | NV. | AN H | MATIT4 | SPITE | 4 87 | Dane | . BW |
| | | 医发送 | DOM: | THE PARTY NAMED IN | C Mark | RECORD | TOR O | e tal | F FOR | M IS PE | OHIZ Market | HTED. | |
| . 338 . | | # 2 Z Z | | 236 | 图 紅漢 | | 216.19 | 1.33 | | | 636 | 2.2 | 1 |

THIS IS UNEVALUATED INFORMATION

25X1X

SOURCE

- 1. Generally, the DIN standards observed in West Germany were also in force for tueis and lubricants in East Germany. They could, however, not always be attained because of raw material difficulties. In such cases, plants in East Germany would apply with the competent production manager of the main administration for a special authorization which generally was granted. Such authorizations were issued by the Liquid Fuels Main Administration of the State Secretarist for Chemistry Plants which, up to late March 1953, received authorizations included the Teerverarbeitungswerke (tar processing plants) Webau, Koepsen, Rositz, and Goelzau which were to produce gasoline with a sulphur content up to 2 percent and a Conradson test up to 0.3 percent, the VEB Mineralcelwerk Luetzkendorf which was to produce a gasoline boiling at 100 degrees of Gelsius on condition that this fuel be mixed with gasoline produced by Synthesewerk Schwarzheide SAG; and the Zeitz and Luetzkendorf plants which were to produce a Diesel oil with a boiling maximum raised from 360 to 375 degrees of Celsius.
- 2. All tar distilling plants were instructed to mix at the ratio of 1 to 1 the Diesel oil they produced with a light Diesel oil produced by the Boehlen plant. Since this measure made it possible for the tar distilling plants to use paraffix oils and light oils for their production, the Diesel oil production could be increased by about 18,000 tons per year.
- 3. Almost the total gasoline production of the tar processing plant was mixed with so-called light gasoline produced by the Schwarzheide plant. This method was adopted because solution gasoline could not be sold. Each ton of solution gasoline produced by SAG Synthesewerk Schwarzheide was paid by the State wath 550 castmarks.

25X1A

Comment. According to the plan, 117,000 tons of solution gasoline were scheduled to be produced by the Schwarzheide lant in 1953.

CLASSIFICATION SECRET/CONTROL - US OFFICIALS ONLY

| STATE | X | NAVY | X | NSRB | 1 | DISTRIBUTION | |
|-------|---|------|----|------|---|--------------|--|
| | X | AIR | 30 | FBI | | OST EV X | |

25X1